

DISCOVERY

Evolution

Discovery Internal Dimensions
140 x 198 x 145cm

James
BAROUD
OFF ROAD TENTS
season proofed

The **Discovery** is the entry level of the James Baroud hard shell tents range, ideal for a lower budget and is the **easiest tent to open and close** because only one side conveniently opens. This tent is also **completely waterproof and wind tested** to the same high standards of the other hard shell tents in the James Baroud range.

Compared to other rooftop tents, the compact size of the **Discovery** reduces the height profile of your vehicle, allowing to travel deeper into those special, **hidden 4WD locations**.

*5 years
guarantee on
fabric, hull and
mechanism





DISCOVERY

Evolution

Construction

- Wind resistance of the tent when opened: 120km/hr
- Reinforced upper and lower hull with stainless steel fittings
- 2 x adjustable safety catches to secure closed
- 2 x built-in aluminium rails to attach the hull onto the roof racks
- 6 x mounting brackets for attaching to roof bars
- Fabric secured to hulls by cable fitted into recessed groove
- 2 x fixing points for the ladder on each side of the hull
- 1 x aluminium ladder (and storage cover), with sliding action to follow vehicle movement
- 1 x removable and rechargeable LED torch

Fabric

- High quality double stitched, aluminised polyester fabric. (6 x ISO ratings)
- Tear resistant mosquito mesh
- Stitched-in elastic drawstring around the tent retracts the fabric when stowing
- 6 x fabric coatings; reflects the sun rays, anti UV, non perishable, 100% waterproof and breathable
- Back door with mosquito mesh, zipper and Velcro fastening, integrated window

Options

- Thermal insulation, gain up to 6° in winter conditions

Guarantee

- 5 years guarantee on fabric, hull and mechanism
- 2 years guarantee on Gelcoat, accessories and ventilation system
- Traceability with the serial number

FABRIC reference		Test Mode
Fabric	100% Polyester	
Coating	Acrylic	
Weight [+/-5%]	240g/m ²	ISO 3801
Dynametic resistance		ISO 19394-1
Warp [5cm]	140 daN	
Weft [5cm]	100 daN	
Resistance to tearing		ISO 13937-1
Warp [4.3cm]	2.0 daN	
Weft [4.3cm]	2.0 daN	
Schmerber	85cm	ISO 811
Resistance to bad weather	6 sides coated	ISO 105 b04

MATTRESS quality		Test Mode
Density	28kg/m ³	ISO 845
Traction resistance	155 kPa	ISO 1798
Air permeability	828L / dm ²	ISO 9237

Distributed in your region by:

